

COMMUNICATION / BATTERIES / BUBBLE MACHINE

DM-28

NETO: 0,00

DYNAMIC MICROPHONE WITH GOOSENECK



DESCRIPTION

Dynamic microphone with gooseneck.

Features:

Optimized for speech transmission, its unidirectional pattern provides highly intelligible sound and ensures clear speech transmission with very little feedback.

Its sturdy, high-quality design provides long-lasting reliability for general use.

It measures 42 cm with a 14 mm Ø gooseneck which is adaptable to desktop bases or microphone stands with standard 5/8" thread.

It features a 3 m fixed cable with a 6.3 mm mono jack connector and an on/off switch, for easy installation and immediate use.

Applications:

For meeting rooms, conferences, religious and educational events, etc.



Expand product information on:
<https://fonestar.com/es/DM-28>

Technical data:

Response 100-12,000 Hz

Sensitivity -56 dB (V/Pa) at 1 kHz

Impedance 600 Ohm

TECHNICAL CHARACTERISTICS

CAPSULE	Unidirectional, dynamic
RESPONSE	100-12,000 Hz
SENSITIVITY	-56 dB (V/Pa) at 1 kHz
IMPEDANCE	600 Ohm
POWER SWITCH	On/off
CABLE	3 m with a 6.3 mm mono jack connector
HEIGHT	Total: 42 cm Robust 14 mm Ø gooseneck, with a standard 5/8" thread female
WEIGHT	0.45 kg



Expand product information on:
<https://fonestar.com/es/DM-28>