

MA-65RGUB

PA SINGLE ZONE AMPLIFIER



DESCRIPTION

PA amplifiers with excellent performance and a variety of inputs and outputs. Suitable for commercial installations, PA installations and distributed audio. Equipped with USB/SD recorder/player, and digital FM tuner.

TECHNICAL CHARACTERISTICS

FEATURES	PA amplifier. USB/SD recorder/player. Digital FM tuner. Phantom power supply. Priority paging.
POWER	90 W maximum, 60 W RMS
RESPONSE	80-16,000 Hz ± 3 dB
DISTORTION	Harmonic: < 0.5%
INPUTS	4 balanced mics./lines, combo (XLR and 6.3 mm jack) 600 Ohm 3 mV RMS and 47,000 Ohm 150 mV RMS, switchable 1 aux, 2 x RCA 47,000 Ohm 250 mV RMS 1 amp in, RCA 10,000 Ohm 1 V RMS 1 tel. input, screw terminals 600 Ohm 100 mV RMS



Expand product information on:
<https://fonestar.com/es/MA-65RGUB>

OUTPUTS	1 line out, 2 x RCA 47,000 Ohm 1 V RMS 1 pre out, RCA 600 Ohm 1 V RMS 1 monitor, screw terminals 600 Ohm, 775 mV RMS and 1 W 8 Ohm (aux input)
CONTROLS	Tone: Bass: ±10 dB Treble: ±10 dB Volume: inputs 1 to 4, aux., general volume, USB/SD player.
PLAYER	USB/SD recorder/player and digital FM tuner with pre-tuned channels and auto scan
PHANTOM	24 V in mics. 1 to 4, selectable
PRIORITY	Tel. input and mic. 1 through signal level, selectable
IMPEDANCE	4 Ohm and 100, 70 and 25 V lines, screw terminals
POWER SUPPLY	230/115 V AC, 130 W and 24 V DC, 82 W
DIMENSIONS	420 x 89 x 300 mm depth. 2 U 19" rack
WEIGHT	8 kg
ACCESSORIES	Mounts for assembly in 19" rack



Expand product information on:
<https://fonestar.com/es/MA-65RGUB>