

MOUNTS / DYNAMIC MICROPHONES / ADAPTERS

PRISMA-55TW

NETO: 0,00

OUTDOOR LOUDSPEAKER



DESCRIPTION

Outdoor speaker BENEFITS Outdoor speaker with 100 V line transformer and low impedance of high quality and power. Its housing is resistant to sunlight (UV), has an aluminum grill with powder paint, protection against water (IP65) and against corrosive materials. All of this makes them highly durable and ideal for outdoor spaces, wet and marine environments. Includes adjustable stainless steel fixing bracket, which minimizes installation time. APPLICATIONS For all types of outdoor installations, wet and marine environments. TECHNICAL DATA 50/40/30/20/10 W RMS @ 100 V and low Z: 8 Ohm Speakers 1 polypropylene mica woofer 5 ¼" 1 mylar tweeter 1" Response 55-20,000 Hz Coverage angle 130 ° Operating temperature -20 ° C to 100° C

TECHNICAL CHARACTERISTICS



Expand product information on:
<https://fonestar.com/es/PRISMA-55TW>

CHARACTERISTICS	Outdoor loudspeaker with 100 V line transformer and low impedance. Sunlight (UV) resistant casing. Aluminium grille with electrostatic paint. Protection against water and anti-corrosive materials.
POWER	100 W maximum, 50 W RMS
LOUDSPEAKERS	1 polypropylene mica woofer 5 ¼" 1 mylar tweeter 1"
RESPONSE	55-20,000 Hz
IMPEDANCE	High Z line 100 V: 200 Ohm (50 W) 250 Ohm (40 W) 330 Ohm (30 W) 500 Ohm (20 W) 1,000 Ohm (10 W) Low Z: 8 Ohm
SENSITIVITY	85 dB at 1 W / 1 m
SOUND PRESSURE	102 dB ± 2 dB at full power at 1 m
DISPERSION	130°
OPERATING TEMPERATURE	-20° C to 100° C
SWITCHES	Selector W in high Z and low Z
PROTECTION	IP65
CROSSOVER	Treble filter
CONNECTORS	Push-in terminals with protection cable gland cover
COLOUR	Black (RAL 9017)
DIMENSIONS	157 x 230 x 170 mm depth
WEIGHT	2*3 kg
ACCESSORIES	Adjustable stainless steel fixing bracket



Expand product information on:
<https://fonestar.com/es/PRISMA-55TW>